


SAYA LED48 SMD G9

|  |  |  |
|--|--|--|
|  |  |  |
|  |  |  |

|           |         |     |          |            |    |     |        |       |        |     |             |       |    |    |
|-----------|---------|-----|----------|------------|----|-----|--------|-------|--------|-----|-------------|-------|----|----|
| 220-240V~ | 50/60Hz | 2,5 | 2,5 - 21 | 48 LED SMD | G9 | 200 | Ra ≥80 | 30000 | ≥15000 | A++ | 3 kWh/1000h | 1-/50 | 25 | CE |
|-----------|---------|-----|----------|------------|----|-----|--------|-------|--------|-----|-------------|-------|----|----|

źródło wykorzystuje diody LED SMD 3528 / light source uses SMD 3528 LEDs

G9 STAR



G9 STAR

| Kanlux      | Kanlux | [W] | [W]     | [lm] | kWh/1000h |
|-------------|--------|-----|---------|------|-----------|
| G9-20W STAR | 18420  | 20  | 20 - 26 | 235  | 20        |
| G9-33W STAR | 18421  | 33  | 33 - 43 | 460  | 33        |
| G9-48W STAR | 18422  | 48  | 48 - 63 | 740  | 48        |
| G9-60W STAR | 18423  | 60  | 60 - 78 | 975  | 60        |

|           |         |    |                 |      |       |   |           |   |    |
|-----------|---------|----|-----------------|------|-------|---|-----------|---|----|
| 220-240V~ | 50/60Hz | G9 | Tc [K] 2700±100 | 2000 | ≥8000 | C | 1/50/1000 | 3 | CE |
|-----------|---------|----|-----------------|------|-------|---|-----------|---|----|